

**1. PRODUCT NAME**

**The Thirties Collection  
Data Sheet**

**2. MANUFACTURER**

**Stonepeak Ceramics, Inc.**  
314 West Superior, Suite 201  
Chicago, IL 60654  
Telephone: 312.506.2800  
Fax: 312.335.0533  
E: [info@stonepeakceramics.com](mailto:info@stonepeakceramics.com)  
W: [www.stonepeakceramics.com](http://www.stonepeakceramics.com)

**3. PRODUCT DESCRIPTION**

**The Thirties**

A highly versatile collection that blends natural simplicity with technical details. The collection includes seven colors in two finishes available in 30"x30" size.

**Recommended Applications:**

Ideally suited for commercial and residential settings such as hotel lobbies, restaurants, shopping malls, airports, schools, and residential floors and walls.

**Finishes/Textures:**

Thru-Color /Rectified Honed & Polished

**Size/thickness:**

30"x30" x 1/3" nominal \* (8 mm)

*\*denotes work size per ISO 10545-2*

**Recommended Grout Joint: 1/8" or greater**

**Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, require the use of leveling tools.**

**For patterns with running bond/brick joints patterns StonePeak recommends a maximum of 33% offset.**

**4. TECHNICAL DATA**

Physical	ASTM Test	Industry Standards	StonePeak Results
Water Absorption	C373	Impervious < 0.5%	≤ 0.1%
Thickness Dimension	C499	Range ±0.04 Inc. Max	≤ ±0.04 Inc.
Facial Dimension	C499	± 0.25%	≤ ±0.25%
Warpage average diagonal	C485	± 0.40%	≤ ±0.40%
Warpage average edge	C485	± 0.40%	≤ ±0.40%
Wedging Average	C502	± 0.25%	≤ ±0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥250 lb	≥ 400 lb
Hardness (Mohs)	Scratch Test ( No regulated)	Range 0 -10	≥7
Visible Abrasion Resistance for Glazed Tiles	C1027	No Requirements Range 0-5	Class 4
Frost Resistance	C1026	No sample must show alterations to surface	No Evidence Of Damage
Chemical Resistance	C650	No Requirement Range E- A	Class A
Stain Resistance	C1378	No Requirement Range E- A	Class A*
DCOF	BOT 3000	≥ 0.42*	≥0.42*
Aesthetic Class/Shade Rating	Visual Evaluation Shade &Texture	No Requirement Range V0 – V4	V2

\* All values given are for matte or honed material. No values are given for polished material. StonePeak does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

**5. INSTALLATION**

Surface preparations:

All installation work using StonePeak Ceramics tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCA Handbook for Ceramic Tile installations.

All substrates should be between 40 degrees F and 90 degrees F and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds as per ANSI A108.01.

Deflection:

Substrate must conform to all state and local building code requirements and ANSI A108.01 for maximum allowable substrate deflection

Movement joints:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; 3.7; A108.02 – 4.4 and TCA Details EJ171.

Installation or setting materials:

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

## 6. AVAILABILITY AND COST

**StonePeak The Thirties Collection** is available from select distributors of ceramic tile.

To find accessible information of delivery and product costs for your area, please contact your nearest StonePeak Ceramics representative.

## 7. WARRANTY

**Stonepeak Ceramics** guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

For further information and details please contact your nearest StonePeak Ceramics Distributor or StonePeak Ceramics representative for a written copy of the warranty information.

**See section 2 for contact information.**

## 8. MAINTENANCE

### Care and Maintenance Recommendations Guide

Please refer to **StonePeak Ceramics Care and Maintenance Recommendations Guide** which is available for download on StonePeak Ceramics website.

## 9. TECHNICAL SERVICES

### Technical Assistance


Guide Specifications, literature, MSDS, tile samples, details and installation procedures are all available for your use or libraries.

Please contact your nearest StonePeak distributor for catalogues or physical samples.

## 10. FILING SYSTEMS

### THE THIRTIES COLLECTION

Statuarietto



Calacatta Oro



Cremino



Bardiglietto




Bianco Carrara



Travertino Grigio



Travertino Chiaro



Note to Specifier: Click on collection with Internet connection to hyperlink directly to product color data at the StonePeak Ceramics website.

## 11. ENVIRONMENTAL CERTIFICATIONS

StonePeak has proudly attained factory and product certifications:



## 12. RECYCLED CONTENT

Products certified by Bureau Veritas. Please ask to see certification

Pre-Consumer Recycled Content  
Post-Consumer Recycled Content